

TG30/15 IP44

ZAPFWELLENGENERATOR



Diese Generatoren bieten viele Möglichkeiten der Stromversorgung für alle landwirtschaftlichen Betriebe.

Leistung

Drei Phasen Leistung COP	kVA	27
Einphasig Leistungs COP	kVA	10.8

Spezifikationen

Spannung	V	400/230
Frequenz	Hz	50
Leistungsfaktor	cos ϕ	0.8/1
Umdrehungen Zapfwelle	U/min	1500
Power (tractor)	kW/HP	51/70
Umdrehungen Zapfwelle	U/min	430
Über- Unterspannungsrelais	%	1.5



Maßangaben

Länge	(L) mm	958
Breite	(W) mm	645
Höhe	(H) mm	1003
Leergewicht	Kg	225

Ausstattungen

ThermomThermomagnetic circuit breaker	X
FI-Schutzschalter	X
Spannungsmesser	X
Frequenzzähler	X
Min - max Voltage controller	X

Steckdosen

SCHUKO 230V 16A IP54	1
3P+N+T CEE 400V 32A IP44	1
3P+N+T CEE 400V 63A	1

Generator- und Steckdosenschutz

Elektro Schutz	IP44
Steckdosenschutz	IP54



The information is aligned with the Data file at the time of download. Printed on 07/02/2024 (ID 2332)

©2024 | PR Industrial S.r.l unipersonale – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

